


Product Data

Material:	PTFE-impregnated Quadrasyn™ composite containing Aramid and Kynol®
Construction:	Interwoven™ braid
pH Range:	2 – 12
Shaft Speed:	1200 fpm
Temperature Limit:	-10°F to 400°F (-23°C to 200°C)
Pressure Limit:	400 psi (2000 psi in plunger pumps)
Sealability:	Lowest clamping pressure to attain low pump leakage



Service

Style 1392S is a general service PTFE-impregnated, high-performance synthetic packing. Engineered to handle a wide variety of service conditions, style 1392S is especially useful in applications including stock pumps, beaters, jordans, hydropulpers, hydrofiners, stock chests, digester pumps, sewage pumps, water pumps, mixer and agitator shafts, blenders and groove gasking.

Style 1392S is braided of our exclusive Quadrasyn™ composite containing Aramid and Kynol™, heavily impregnated with virgin PTFE dispersion and saturated with our proprietary high-temperature lubricant. Since no graphite is used in its construction, style 1392 cannot discolor fluids being pumped.

Style 1392S is recommended for general service in such fluids as air, oils, water, steam, brines and many mild to moderately reactive chemicals. (Available in rectangular cross-sections.)

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1 1/8"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,10	—
Length (±10%)	ft/lb	76.90	36.00	21.20	14.50	10.89	7.30	6.56	4.45	3.68	3.19	2.93	2.29	1.95	1.74	1.55	1.00
	M/kg	51,69	24,10	14,25	9,70	7,20	4,80	4,39	2,99	2,47	2,14	1,96	1,54	1,31	1,17	1,04	0,67
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.																

Distributed by

A Greene, Tweed Company
Denton Industrial Park
25 Engerman Ave., Denton, MD 21629
Phone: +1.410.479.2244, Fax: +1.410.479.0836
E-mail: info@palmettopackings.com
Website: www.palmettopackings.com

Product data is based upon our experience and knowledge of typical applications and should be used to determine approximate service compatibility.

All trademarks are property of their respective owners.
Printed in USA ©2014 Palmetto®
08/14-GT DS-US-PI-190