

Product Data

Material:	PTFE impregnated 95% assay carbon yarn
Construction:	Interwoven™ braid
Temperature Limit:	-400°F to 600°F (-240°C to 315°C)
pH Range:	1 – 14
Pressure Limit:	500 psi
Shaft Speed:	3000 fpm



Service

1588 is recommended for use in acids, caustics, solvents, oils, chemicals, paper stock, bleach, liquors and steam.

Typical Applications

1588 is designed for papermill and chemical equipment (jordans, refiners, liquor pumps, chemical pumps, digesters, chlorine pumps, blow pumps, agitators, steaming vessels, top separators and valves). Also effective in reciprocating plunger pumps.

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"
	mm		3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80
Length	ft/lb	111.00	51.00	29.50	20.00	14.07	8.23	7.70	6.00	5.23	4.15	3.48	3.05	2.72	2.32	2.05
	M/kg	74,40	34,20	19,80	13,40	9,43	5,51	5,16	4,02	3,50	2,78	2,33	2,04	1,82	3,46	1,37
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.															

Distributed by

A Greene, Tweed Company
Denton Industrial Park
25 Engerman Ave., Denton, MD 21629
Phone: +1.410.479.2244, Fax: +1.410.479.0836
E-mail: info@palmettopackings.com
Website: www.palmettopackings.com