

Product Data

Material: Inconel[®] wire inserted carbon yarn with a pliable core/corrosion inhibitor
 Construction: Braid over homogeneous core
 Temperature Limit: -10°F (-23°C) to 1200°F (649°C)
 Pressure Limit: 1200 psi (83 bar)



Service

Style 4062AF is comprised of Inconel wire inserted carbon yarn braided over a resilient homogeneous core of graphite and other proprietary materials including a corrosion inhibitor. Easily installed, style 4062AF does not harden in service, making for easy adjustment and removal.

Applications

- Steam valves
- Expansion joints
- Sootblowers
- Exhaust joints

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	7/8"	1"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	22,20	25,40
Length	ft/lb	84.65	47.71	20.83	14.34	11.36	7.11	5.84	5.00	4.01	3.50	3.01	2.00	1.68
	M/kg	56,72	31,97	13,96	9,61	7,61	4,76	3,91	3,35	2,69	2,35	2,02	1,34	1,13
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.													

Distributed by

A Greene, Tweed Company
 Denton Industrial Park
 25 Engerman Ave., Denton, MD 21629
 Phone: +1.410.479.2244, Fax: +1.410.479.0836
 E-mail: info@palmettopackings.com
 Website: www.palmettopackings.com

