

Product Data

Material:	Pure flexible graphite yarn impregnated with high-temperature resin and inert lubricant
Construction:	Interwoven™ braid
pH Range:	0 – 14 (except fuming nitric, aqua regia and molten alkali metals)
Frictional Drag:	Lowest of all packings
Heat Dissipation:	Equal to pure graphite packings
Temperature Limit:	-400°F to 700°F (-240°C to 370°C)
Pressure Limit:	250 psi (17 bar) in pumps



Service

Pinnacle™ combines unmatched heat dissipation, sealability and lubricity to form a packing with extended service life and virtually zero shaft scoring at low-leak off in pumps (no flush required). In valves, an exclusive passive corrosion inhibitor prevents stem pitting.

Typical Applications

· All rotating applications including general service and acid pumps.

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
	mm		3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	19,10	22,20
Length	ft/lb	62.00	36.20	25.00	17.08	12.10	9.00	7.00	5.60	4.85	3.06	2.20	2.05
	M/kg	41,54	24,25	16,75	11,44	8,11	6,03	4,69	3,75	3,25	2,05	1,47	1,37
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.												

Distributed by

A Greene, Tweed Company
Denton Industrial Park
25 Engerman Ave., Denton, MD 21629
Phone: +1.410.479.2244, Fax: +1.410.479.0836
E-mail: info@palmettopackings.com
Website: www.palmettopackings.com